Homeline 3 Pole Specifications

Type: Square D Homeline Circuit Breakers

Connections: Plug-in type

Pole Spacing: 3-Pole, common trip

Amperage Ratings: 15A, 20A, 30A, 40A, 50A, 60A, 70A, 80A, 100A

Voltage: 208Y/120V AC Max.

Interrupting Rating: 10,000A

Standards: CSA Standard C22.2 No. 5 – Molded-Case Circuit Breakers, Molded-Case Switches and Circuit-Breaker Enclosures

Wire Temperature Ratings and Tightening Torque:

Breaker Rating (A)	AL/CU (60˚/75˚C)	CU (60˚/75˚C)	AL/CU (75˚C Only)	Tightening Torque (lb. inch)
15-30	14-8	14-10		36
40-70	8		6-2	45
80-100			12-2/0	50

Notes:

1. Mechanism is trip free of the handle which assumes a mid position between “ON” and “OFF” upon automatic tripping.
2. These circuit breakers are uncompensated and calibrated to 40˚C requirements.
3. These circuit breakers are suitable for use with copper and aluminum conductors.
4. These circuit breakers are suitable for reversed line and load connections.
5. These circuit breakers may be marked with a high current interrupting rating of 10,000 rms symmetrical amperes at 208Y/120V ac.